

Using Custom Software and Hardware rather than ThermalPro

Frequently Asked Question #18

Question:

I have my own LabView based software and acquisition board for taking data on my PC. We have recently developed some software for processing hotwire anemometry signals. Now we would like to buy a hotwire probe so we can start to measure velocities in our wind tunnel. Which probe should we buy?

Answer:

First we commend you for all your effort developing the data acquisition system and software for thermal anemometry. You do, however, need more than a probe in order to start measuring velocities. We recommend the 1750A Constant Temperature Anemometer with Power Supply. You also get a free probe cable with the 1750A. For electronics, you have your own acquisition board & software. You should use a signal conditioner with variable gain & offset to bring the signals up from the original $2.0 \pm 1V$ to the range of your A/D board, e.g. $\pm 5V$.

For calibration, you would have to do that yourself too, since it is part of the ThermalPro/IFA300 software/hardware package from TSI. Having access to a small wind tunnel or other stable velocity source makes calibration much easier. Customers typically use a pitot tube or other reference measurement for the calibration.



TSI Incorporated - 500 Cardigan Road, Shoreview, MN 55126-3996 USA
USA Tel: +1 800 874 2811 E-mail: fluid@tsi.com Website: www.tsi.com
UK Tel: +44 149 4 459200 E-mail: tsuuk@tsi.com Website: www.tsiinc.co.uk
France Tel: +33 491 95 21 90 E-mail: tsifrance@tsi.com Website: www.tsiinc.fr
Germany Tel: +49 241 523030 E-mail: tsigmbh@tsi.com Website: www.tsiinc.de
Sweden Tel: +46 8 595 13230 E-mail: tsiab@tsi.com Website: www.tsi.se
India Tel: +91 80 41132470 E-mail: tsi-india@tsi.com
China Tel: +86 10 8260 1595 E-mail: tsibeijing@tsi.com

Contact your local TSI Distributor or visit our website www.tsi.com for more detailed specifications.



TRUST. SCIENCE. INNOVATION.